



## FEATURES

- Portable, separate workstations quick and easy
- Static dissipative clear window with conductive Fluted Plastek border
- Flanged material on the bottom allow panels to stand upright
- No need for tape or fasteners
- Economical ESD barrier solution between workstations
- Cleanable with standard IPA/water solutions
- Window Size (H x W) 13" x 21"
- Overall Size (L x W x H) 30" x 6-1/4" x 20"

## PLASTIC MATERIAL SPECIFICATIONS

Properties	Typical Value
Resin Type:	Polypropylene
Conductive:	Inherently
Surface Resistance:	$1 \times 10^2$ to $< 1 \times 10^5$ ohms per ANSI/ESD STM11.11
Humidity Independent:	Yes
Temperature Tolerance:	-17° F to +230° F
Melting Point:	324° F

## CLEAR PLASTIC SPECIFICATIONS

Properties	Typical Value
Surface Resistance:	$1 \times 10^5$ to $< 1 \times 10^7$ ohms per ANSI/ESD STM11.11
Static Decay:	< .5 seconds per FTMS-101C
Thickness:	0.02"

*Specifications and procedures subject to change without notice.*

Made in the United States of America  
with Globally Sourced Materials

*Dimensional tolerances are +/- 10% unless otherwise specified*

## PORTABLE ESD SAFETY SHIELD

# PROTEKTIVE PAK

PROTEKTIVE PAK  
13520 MONTE VISTA AVENUE, CHINO, CA 91710  
PHONE (909) 627-2578  
[ProtektivePak.com](http://ProtektivePak.com)

**DRAWING  
NUMBER**  
39370

**DATE:**  
June  
2020