



MB312 PCB Terminal Block, Single Mold



MB312-254



MB312-500



MB

DIMENSIONS/POSITIONS		MB312-254	MB312-500
間距	Pitch	2.54mm	5.00mm
位數	Poles	2 ~ 24Poles	2 ~ 24Poles
塑膠本體	Housing Material	PA 66	PA 66
壓線圈	Cage Clamp	Brass, Ni Plated	Brass, Ni Plated
端子	Contact	Brass, Tin Plated	Brass, Tin Plated
螺紋	Screw Thread	M1.6, Steel, Zinc Plated	M2.6, Steel, Zinc Plated
電線線徑	Wire Size	20 ~ 26AWG	12 ~ 26AWG
剝線長度	Wire Strip Length	4.5mm	7mm
PCB孔徑	PCB Hole Diameter	1.2mm	1.5mm
最大緊固扭矩	Tightening Torque, Max.	1.32 Lb-in	5.0 Lb-in
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

TECHNICAL DATA

連接符合標準 Connection in acc. with standard EN-VDE			
額定電流 I_n	Nominal Current I_n	6A	16A
額定橫截面	Nominal Cross Section	2.5mm ²	2.5mm ²
最大負載電流	Maximum load current	6A	16A
絕緣材料	Insulating Material	PA	PA
阻燃等級,符合UL94 Inflammability class acc. to UL94		V0	V0
額定電壓,UL/CUL Nominal voltage, UL/CUL		125V	300V
額定電流,UL/CUL Nominal current, UL/CUL		6A	16A

